

Insulating gland, DP...HML

FEATURES & BENEFITS

- ✓ brass glands with long metric threads for thick-walled enclosures
- ✓ highest degree of protection - IP68 (with sealing washer)
- ✓ set includes fixing nut

MECHANICAL DATA

Material	body: polyamide 6; seal - CR
Halogen-free	yes
Colour	grey (RAL 7035)
Operating temperature [°C]	-30 ÷ +80

DIMENSIONS


E	15
---	----

CERTIFICATES & STANDARDS

IP degree of protection	IP68 (with sealing washer)
Flammability class	UL 94 V2
Standards	EN 50262; type A

NOTE!

Gland and nut in a kit, without sealing washer.



Type	Index Ergom	L	For spanner A	M thread	Cable external diameter [mm]	Quantity in package [pcs]
DP 16HML (100 PCS)	E03DK-01050100101	24	22	M16x1,5	5,0÷10,0	100
DP 16HML (10 PCS)	E03DK-01050100103	24	22	M16x1,5	5,0÷10,0	10
DP 20 HML (100 PCS)	E03DK-01050100201	28	24	M20x1,5	6,0÷12,0	100
DP 20 HML (10 PCS)	E03DK-01050100203	28	24	M20x1,5	6,0÷12,0	10
DP 20 HML 2 (100 PCS)	E03DK-01050100301	32	27	M20x1,5	10,0÷14,0	100
DP 20 HML 2 (10 PCS)	E03DK-01050100303	32	27	M20x1,5	10,0÷14,0	10
DP 25 HML (50 PCS)	E03DK-01050100401	36	33	M25x1,5	13,0÷18,0	50
DP 25 HML (10 PCS)	E03DK-01050100403	36	33	M25x1,5	13,0÷18,0	10

