

Brass gland, MDW...HL type

FEATURES & BENEFITS

- ✓ long-thread brass glands for thick-walled enclosures, PG threads
- ✓ highest degree of protection - IP68 (factory-mounted O-ring)
- ✓ for indoor and outdoor use

MECHANICAL DATA


Material	body: nickel-plated brass; sealing ring: neoprene; clamping insert: PA 6; o-ring: NBR
Operating temperature [°C]	-40 ÷ +100

CERTIFICATES & STANDARDS

IP degree of protection	IP68
Standards	EN 62444; type A

NOTE!

MDN Nuts are to be ordered separately.



CE

Type	Index Ergom	E	L	For spanner A	For spanner B	PG thread	Cable external diameter [mm]	Quantity in package [pcs]
MDW 7HL (10 PCS)	E03DK-03080100103	10	20	14	14	PG7	3,0÷6,5	10
MDW 9HL (10 PCS)	E03DK-03080100203	10	21	17	17	PG9	4,0÷8,0	10
MDW 11HL (10 PCS)	E03DK-03080100303	10	22	20	20	PG11	5,0÷10,0	10
MDW 13HL (10 PCS)	E03DK-03080100403	10	22	22	22	PG13,5	6,0÷12,0	10
MDW 16HL (10 PCS)	E03DK-03080100503	10	24	24	24	PG16	10,0÷14,0	10
MDW 21HL (10 PCS)	E03DK-03080100603	12	28	30	30	PG21	13,0÷18,0	10
MDW 29HL (10 PCS)	E03DK-03080100703	12	32	40	40	PG29	18,0÷25,0	10
MDW 36HL (10 PCS)	E03DK-03080100803	15	38	50	50	PG36	22,0÷32,0	10
MDW 42HL	E03DK-03080100903	15	42	58	58	PG42	30,0÷38,0	1
MDW 48HL	E03DK-03080101003	18	44	64	64	PG48	34,0÷44,0	1

