




Brass gland, MDW...HML type

FEATURES & BENEFITS

-  long-thread brass glands for thick-walled enclosures, M threads
-  highest degree of protection - IP68 (factory-mounted O-ring)
-  for indoor and outdoor use

MECHANICAL DATA


Material	body: nickel-plated brass; sealing ring: neoprene; clamping insert: PA 6; o-ring: NBR
Operating temperature [°C]	-40 ÷ +100

CERTIFICATES & STANDARDS

IP degree of protection	IP68
Standards	EN 62444; type A

NOTE!

MDN Nuts are to be ordered separately.



Type	Index Ergom	E	L	For spanner A	For spanner B	M thread	Cable external diameter [mm]	Quantity in package [pcs]
MDW 12HML (10 PCS)	E03DK-03080200103	12	20	14	14	M12x1,5	3÷6,5	10
MDW 16HML (10 PCS)	E03DK-03080200203	12	21	17	18	M16x1,5	4÷8	10
MDW 20HML (10 PCS)	E03DK-03080200303	12	22	22	22	M20x1,5	6÷12	10
MDW 25HML (10 PCS)	E03DK-03080200403	12	24	24	27	M25x1,5	10÷14	10
MDW 32HML (10 PCS)	E03DK-03080200503	15	28	30	34	M32x1,5	13÷18	10
MDW 40HML (10 PCS)	E03DK-03080200603	15	32	40	43	M40x1,5	18÷25	10
MDW 50HML	E03DK-03080200703	15	46	50	55	M50x1,5	22÷32	1
MDW 63HML	E03DK-03080200803	18	44	64	68	M63x1,5	34÷44	1

