

Unslotted trunking, KN type

FEATURES & BENEFITS

- cable bundle trunking in office, production, etc. facilities
- wide range of connecting and branching accessories

LOGISTIC DATA

Quantity in package [pcs] 1

SES separators and CO holders can be mounted

MECHANICAL DATA

Material PCV
 Operating temperature [°C] -20 ÷ +60
 Colour white (RAL 9001)
 Shock resistance IK 08 (5J)

DIMENSIONS


Length [m] 2

CERTIFICATES & STANDARDS

IP degree of protection IP40
 Flammability class UL 94 V0
 Standards EN 50085-1; EN 50085-2-3

NOTE!

Bottom holes in line with KOPD Guidebook.



Type	Index Ergom	B	H	Number of separators [pcs]
KN 15X17/2	E02KK-02010100101	15	17	
KN 20X10/2	E02KK-02010100201	20	10	
KN 25X80/2	E02KK-02010100701	25	80	
KN 30X10/2	E02KK-02010100801	30	10	
KN 40X10/2	E02KK-02010100901	40	10	
KN 40X80/2	E02KK-02010101401	40	80	
KN 40X100/2	E02KK-02010101421	40	100	
KN 60X17/2	E02KK-02010101501	60	17	
KN 80X100/2	E02KK-02010102121	80	100	
KN 100X40/2	E02KK-02010102201	100	40	2