

Insulating fiberglass tubes, OSKS/5 type

FEATURES & BENEFITS




electrical insulating sleeve for high-temperature operation up to 180°C and breakdown strength of 5kV



excellent electric and mechanical properties



wide range of diameters



APPLICATION

Insulation of LV cables and wires operating at increased temperatures

MECHANICAL DATA

Material	fiberglass impregnated with silicone rubber
Operating temperature [°C]	-40 ÷ +180
Flammability	self-extinguishing
Colour	white

ELECTRICAL DATA

Breakdown strength [kV]	5
-------------------------	---



CERTIFICATES & STANDARDS

Flammability class	VW-1 according to UL 1441
Standards	PN-EN 60684-1 point 7, point 5 - class4 PN-EN 60684-2:2011E point 3, 13, 14, 21.1-21.2 PN-EN 60684-3-400 do 402: 2003(U) table 5

Type	Index Ergom	Inside diameter A [mm]	Wall thickness B [mm]	Quantity in package [m]
OSKS/5-1 (200 M)	E05ME-03010400101	1	0,4	200
OSKS/5-2 (200 M)	E05ME-03010400201	2	0,4	200
OSKS/5-3 (100 M)	E05ME-03010400301	3	0,5	100
OSKS/5-4 (100 M)	E05ME-03010400401	4	0,5	100
OSKS/5-5 (100 M)	E05ME-03010400501	5	0,5	100
OSKS/5-6 (100 M)	E05ME-03010400601	6	0,5	100
OSKS/5-7 (100 M)	E05ME-03010400701	7	0,6	100
OSKS/5-8 (50 M)	E05ME-03010400801	8	0,6	50
OSKS/5-10 (50 M)	E05ME-03010401001	10	0,7	50
OSKS/5-12 (50 M)	E05ME-03010401201	12	0,7	50
OSKS/5-14 (50 M)	E05ME-03010401401	14	0,7	50
OSKS/5-16 (50 M)	E05ME-03010401601	16	0,7	50