






Steel fitting for protective conduits, MWO...S type

FEATURES & BENEFITS

-  stainless-steel connectors for WO...S conduits, standard industrial conditions
-  to route cables protected by WOS, WOT piping into enclosures
-  together with WOT conduits, ensures IP66 degree of protection
-  high mechanical and impact strength, resistance to difficult ambient conditions



LOGISTIC DATA

Quantity in package [pcs] 1

Recommended for WO...S conduits. The tube is screwed into the gland.

MECHANICAL DATA

Material stainless steel+ polyethylene insert
 Halogen-free yes
 Operating temperature [°C] -30 ÷ +80

CERTIFICATES & STANDARDS

IP degree of protection IP66

NOTE!

MDN...ST nuts and gland seals have to be ordered separately.



| Type | Index Ergom | For spanner A | For spanner B | L | C | E | PG thread |
|-------------|-------------------|---------------|---------------|------|------|----|-----------|
| MWO 7S | E03DK-08020100103 | 19 | 17 | 10,0 | 7,5 | 6 | PG7 |
| MWO 9S | E03DK-08020100203 | 22 | 20 | 12,5 | 9,2 | 6 | PG9 |
| MWO 11S | E03DK-08020100303 | 27 | 24 | 13,0 | 11,9 | 7 | PG11 |
| MWO 13S | E03DK-08020100403 | 29 | 26 | 13,0 | 13,6 | 7 | PG13,5 |
| MWO 16S | E03DK-08020100503 | 30 | 30 | 16,5 | 15,3 | 8 | PG16 |
| MWO 21S | E03DK-08020100603 | 36 | 34 | 16,5 | 20,2 | 8 | PG21 |
| MWO 29S | E03DK-08020100703 | 47 | 45 | 19,5 | 26,7 | 8 | PG29 |
| MWO 36S | E03DK-08020100803 | 60 | 56 | 26,5 | 34,6 | 10 | PG36 |
| MWO 48S NFC | E03DK-08020100903 | 74 | 70 | 33,0 | 45,3 | 10 | PG48 NFC |

