

FEATURES & BENEFITS

- sheet metal edge shields in enclosures at wire and cable routing points
- protects wire insulation from damage
- for a wide range of enclosure wall thickness




MECHANICAL DATA

Material	PCV resistant to typical solvents, lubricants, oils, sea water, moulds etc.
Operating temperature [°C]	-30 ÷ +70
Assembly temperature [°C]	-5 ÷ +35

NOTE!

RD, BL, GY, WT, YL colours on request - for details visit www.ergom.com



Type	Index Ergom	Colour	Metal plate thickness [mm]	A	B	E	Quantity in package [m]
OKU 1/0,5 (50 M)	E01PK-01060100100	black	0,4+0,7	3,5	7,5	0,5	50
OKU 1/0,5 BL (50 M)	E01PK-01060110100	blue	0,4+0,7	3,5	7,5	0,5	50
OKU 1/0,5 GY (50 M)	E01PK-01060110200	grey	0,4+0,7	3,5	7,5	0,5	50
OKU 1/0,5 RD (50 M)	E01PK-01060110300	red	0,4+0,7	3,5	7,5	0,5	50
OKU 1/0,5 WT (50 M)	E01PK-01060110400	white	0,4+0,7	3,5	7,5	0,5	50
OKU 1/0,5 YL (50 M)	E01PK-01060110500	yellow	0,4+0,7	3,5	7,5	0,5	50
OKU 2/1 (50 M)	E01PK-01060100300	black	0,8+1,2	4,5	9,5	0,5	50
OKU 2/1 BL (50 M)	E01PK-01060110600	blue	0,8+1,2	4,5	9,5	0,5	50
OKU 2/1 GY (50 M)	E01PK-01060110700	grey	0,8+1,2	4,5	9,5	0,5	50
OKU 2/1 RD (50 M)	E01PK-01060110800	red	0,8+1,2	4,5	9,5	0,5	50
OKU 2/1 WT (50 M)	E01PK-01060110900	white	0,8+1,2	4,5	9,5	0,5	50
OKU 2/1 YL (50 M)	E01PK-01060111000	yellow	0,8+1,2	4,5	9,5	0,5	50
OKU 3/1,5 (50 M)	E01PK-01060100500	black	1,2+1,8	5,0	10,0	0,5	50
OKU 3/1,5 BL (50 M)	E01PK-01060111100	blue	1,2+1,8	5,0	10,0	0,5	50
OKU 3/1,5 GY (50 M)	E01PK-01060111200	grey	1,2+1,8	5,0	10,0	0,5	50
OKU 3/1,5 RD (50 M)	E01PK-01060111300	red	1,2+1,8	5,0	10,0	0,5	50
OKU 3/1,5 WT (50 M)	E01PK-01060111400	white	1,2+1,8	5,0	10,0	0,5	50
OKU 3/1,5 YL (50 M)	E01PK-01060111500	yellow	1,2+1,8	5,0	10,0	0,5	50
OKU 4/2 (25 M)	E01PK-01060100700	black	1,7+2,3	5,5	10,5	1,0	25
OKU 4/2 BL (25 M)	E01PK-01060111600	blue	1,7+2,3	5,5	10,5	1,0	25
OKU 4/2 GY (25 M)	E01PK-01060111700	grey	1,7+2,3	5,5	10,5	1,0	25
OKU 4/2 RD (25 M)	E01PK-01060111800	red	1,7+2,3	5,5	10,5	1,0	25
OKU 4/2 WT (25 M)	E01PK-01060111900	white	1,7+2,3	5,5	10,5	1,0	25
OKU 4/2 YL (25 M)	E01PK-01060112000	yellow	1,7+2,3	5,5	10,5	1,0	25
OKU 5/2,5 (25 M)	E01PK-01060100900	black	2,2+2,8	6,5	12,5	1,0	25
OKU 5/2,5 BL (25 M)	E01PK-01060112100	blue	2,2+2,8	6,5	12,5	1,0	25
OKU 5/2,5 GY (25 M)	E01PK-01060112200	grey	2,2+2,8	6,5	12,5	1,0	25
OKU 5/2,5 RD (25 M)	E01PK-01060112300	red	2,2+2,8	6,5	12,5	1,0	25
OKU 5/2,5 WT (25 M)	E01PK-01060112400	white	2,2+2,8	6,5	12,5	1,0	25
OKU 5/2,5 YL (25 M)	E01PK-01060112500	yellow	2,2+2,8	6,5	12,5	1,0	25
OKU 6/3 (25 M)	E01PK-01060101100	black	2,7+3,3	7,5	13,0	1,5	25

Type	Index Ergom	Colour	Metal plate thickness [mm]	A	B	E	Quantity in package [m]
OKU 6/3 BL (25 M)	E01PK-01060112600	blue	2,7+3,3	7,5	13,0	1,5	25
OKU 6/3 GY (25 M)	E01PK-01060112700	grey	2,7+3,3	7,5	13,0	1,5	25
OKU 6/3 RD (25 M)	E01PK-01060112800	red	2,7+3,3	7,5	13,0	1,5	25
OKU 6/3 WT (25 M)	E01PK-01060112900	white	2,7+3,3	7,5	13,0	1,5	25
OKU 6/3 YL (25 M)	E01PK-01060113000	yellow	2,7+3,3	7,5	13,0	1,5	25
OKU 7/3,5 (25 M)	E01PK-01060101300	black	3,3+3,8	7,5	14,0	1,5	25
OKU 7/3,5 BL (25 M)	E01PK-01060113100	blue	3,3+3,8	7,5	14,0	1,5	25
OKU 7/3,5 GY (25 M)	E01PK-01060113200	grey	3,3+3,8	7,5	14,0	1,5	25
OKU 7/3,5 RD (25 M)	E01PK-01060113300	red	3,3+3,8	7,5	14,0	1,5	25
OKU 7/3,5 WT (25 M)	E01PK-01060113400	white	3,3+3,8	7,5	14,0	1,5	25
OKU 7/3,5 YL (25 M)	E01PK-01060113500	yellow	3,3+3,8	7,5	14,0	1,5	25
OKU 8/4 (25 M)	E01PK-01060101500	black	3,7+4,3	8,5	14,0	2,0	25
OKU 8/4 BL (25 M)	E01PK-01060113600	blue	3,7+4,3	8,5	14,0	2,0	25
OKU 8/4 GY (25 M)	E01PK-01060113700	grey	3,7+4,3	8,5	14,0	2,0	25
OKU 8/4 RD (25 M)	E01PK-01060113800	red	3,7+4,3	8,5	14,0	2,0	25
OKU 8/4 WT (25 M)	E01PK-01060113900	white	3,7+4,3	8,5	14,0	2,0	25
OKU 8/4 YL (25 M)	E01PK-01060114000	yellow	3,7+4,3	8,5	14,0	2,0	25
OKU 9/4,5 (25 M)	E01PK-01060101700	black	4,2+4,8	9,5	15,5	2,0	25
OKU 9/4,5 BL (25 M)	E01PK-01060114100	blue	4,2+4,8	9,5	15,5	2,0	25
OKU 9/4,5 GY (25 M)	E01PK-01060114200	grey	4,2+4,8	9,5	15,5	2,0	25
OKU 9/4,5 RD (25 M)	E01PK-01060114300	red	4,2+4,8	9,5	15,5	2,0	25
OKU 9/4,5 WT (25 M)	E01PK-01060114400	white	4,2+4,8	9,5	15,5	2,0	25
OKU 9/4,5 YL (25 M)	E01PK-01060114500	yellow	4,2+4,8	9,5	15,5	2,0	25
OKU 10/5 (25 M)	E01PK-01060101900	black	4,6+5,4	10,5	16,5	2,0	25
OKU 10/5 BL (25 M)	E01PK-01060114600	blue	4,6+5,4	10,5	16,5	2,0	25
OKU 10/5 GY (25 M)	E01PK-01060114700	grey	4,6+5,4	10,5	16,5	2,0	25
OKU 10/5 RD (25 M)	E01PK-01060114800	red	4,6+5,4	10,5	16,5	2,0	25
OKU 10/5 WT (25 M)	E01PK-01060114900	white	4,6+5,4	10,5	16,5	2,0	25
OKU 10/5 YL (25 M)	E01PK-01060115000	yellow	4,6+5,4	10,5	16,5	2,0	25
OKU 11/5,5 (25 M)	E01PK-01060102100	black	5,1+5,9	11,5	17,5	2,0	25
OKU 11/5,5 BL (25 M)	E01PK-01060115100	blue	5,1+5,9	11,5	17,5	2,0	25
OKU 11/5,5 GY (25 M)	E01PK-01060115200	grey	5,1+5,9	11,5	17,5	2,0	25
OKU 11/5,5 RD (25 M)	E01PK-01060115300	red	5,1+5,9	11,5	17,5	2,0	25
OKU 11/5,5 WT (25 M)	E01PK-01060115400	white	5,1+5,9	11,5	17,5	2,0	25
OKU 11/5,5 YL (25 M)	E01PK-01060115500	yellow	5,1+5,9	11,5	17,5	2,0	25
OKU 12/6 (25 M)	E01PK-01060102300	black	5,6+6,4	12,0	19,0	2,0	25
OKU 12/6 BL (25 M)	E01PK-01060115600	blue	5,6+6,4	12,0	19,0	2,0	25
OKU 12/6 GY (25 M)	E01PK-01060115700	grey	5,6+6,4	12,0	19,0	2,0	25
OKU 12/6 RD (25 M)	E01PK-01060115800	red	5,6+6,4	12,0	19,0	2,0	25
OKU 12/6 WT (25 M)	E01PK-01060115900	white	5,6+6,4	12,0	19,0	2,0	25
OKU 12/6 YL (25 M)	E01PK-01060116000	yellow	5,6+6,4	12,0	19,0	2,0	25

