Blind reducing sealing ring, UPR

FEATURES & BENEFITS



replaceable PVC rings for MDW cable gland modification



smaller diameter cable can be mounted

LOGISTIC DATA

Can be used instead of a standard ring. If a standard ring is too large for the cable used it may be replaced with a reducing ring.

APPLICATION

for MDW glands (IP54)

MECHANICAL DATA

Material	PCV
Operating temperature [°C]	-20 ÷ +80





Туре	Index Ergom	Α	В	Reducer	Cable gland thread	Cable external diameter [mm]
UPR 9/7 (10 PCS)	E03DK-02100100103	13,3	5,5	9/7	PG9	3,5-6,5
UPR 11/9 (10 PCS)	E03DK-02100100203	16,7	5,5	11/9	PG11	5,5-8,7
UPR 13/9 (10 PCS)	E03DK-02100100303	18,5	5,5	13/9	PG13,5	5,5-8,7
UPR 13/11 (10 PCS)	E03DK-02100100403	18,5	5,5	13/11	PG13,5	7,0-10,5
UPR 16/9 (10 PCS)	E03DK-02100100503	20,0	6,0	16/9	PG16	5,5-8,7
UPR 16/11 (10 PCS)	E03DK-02100100603	20,6	6,0	16/11	PG16	7,0-10,5
UPR 16/13 (10 PCS)	E03DK-02100100703	20,6	6,0	16/13	PG16	8,0-12,5
UPR 21/16 (10 PCS)	E03DK-02100100803	25,6	7,3	21/16	PG21	10,0-15,0



14/1/2025