

## FEATURES & BENEFITS

- cable ties for chemical industry, galvanising plants, etc.
- resistant to water in low temperatures

## LOGISTIC DATA

Quantity in package [pcs] 100

## MECHANICAL DATA

Material polypropylene (PP)  
 Halogen-free yes  
 Colour green  
 Operating temperature [°C] -20 ÷ +85  
 Minimum installation temperature [°C] 0

## CERTIFICATES & STANDARDS

Flammability class HB wg. UL 94  
 Standards EN IEC 62275:2019



Type	Index Ergom	Tensile strength, min. [daN]	Max. bundle dia. [mm]	Tool type	L	W
TKPP 9/3 (100 PCS)	E01TK-01110100101	5	22	MK III A, MK III PR	99	2,5
TKPP 20/5 (100 PCS)	E01TK-01110100201	13	51	MK III A, MK III B, MK III C, MK III PR	213	4,8
TKPP 30/5 (100 PCS)	E01TK-01110100301	13	76	MK III A, MK III B, MK III C, MK III PR	290	4,8
TKPP 40/5 (100 PCS)	E01TK-01110100401	13	102	MK III A, MK III B, MK III C, MK III PR	368	4,8
TKPP 30/8 (100 PCS)	E01TK-01110100601	22	76	MK III B, MK III C	292	7,6
TKPP 40/8 (100 PCS)	E01TK-01110100701	22	102	MK III B, MK III C	368	7,6