

Insulated spade terminals in heat-shrink insulation, KWIT type

FEATURES & BENEFITS

- spade terminal Cu, with heat-shrink insulating sleeve with adhesive, marked with screw size and cable cross-section
- heat-shrink insulation; enhances resistance to vibrations, mitigates short-circuit risk
- sleeve colours facilitate cross-section identification
-

LOGISTIC DATA

Quantity in package [pcs] 100

MECHANICAL DATA


Insulation heat-shrink sleeve
 Material Cu
 Surface tin-plated
 Operating temperature [°C] -55 ÷ +105
 Shrink temperature [°C] > 120

CERTIFICATES & STANDARDS

Design copper part of terminals acc. to DIN 46234 sizes

NOTE!

Other designs on request.



Type	Index Ergom	Cross-section [mm ²]	Insulation colour	Screw hole	L	d	D	e	W	Weight [kg]
KWIT 1/4 (100 PCS)	E09KO-02070300201	0,5+1	red	M4	30	1,6	4,8	21	8,2	0,07
				M5						0,09
KWIT 2,5/4 (100 PCS)	E09KO-02070300401	1,5+2,5	blue	M4	30	2,2	5,8	21	9	0,08
				M5						0,1
KWIT 6/4 (100 PCS)	E09KO-02070300601	4+6	yellow	M4	34	3,4	6,8	25	9,2	0,15
				M5						0,17