





# Insulated “butt splice” connectors, KLI type

## FEATURES & BENEFITS

-  connector Cu, with polyamide insulation, to make “butt splice” cable connections
-  central stamping guarantees correct length of conductor insertion
-  insulating sleeve: enhances resistance to vibrations, mitigates short-circuit risk, facilitates cable installation
-  sleeve colours facilitate cross-section identification

## LOGISTIC DATA

Quantity in package [pcs] 100

## MECHANICAL DATA

Insulation polyamide 6.6

Material Cu

Surface tin-plated


Operating temperature [°C] -30 ÷ +95

## CERTIFICATES & STANDARDS

Technical approval PRS TE/2241/880567/19



A-A



**EAC**

Type	Index Ergom	Cross-section [mm <sup>2</sup> ]	Insulation colour	L <sub>1</sub>	L <sub>2</sub>	d <sub>1</sub>	d <sub>2</sub>	Weight [kg]
<b>KLI 0,5 (100 PCS)</b>	E09KO-02060100101	0,2÷0,5	yellow	20,0	12	1,3	2,0	0,04
<b>KLI 1 (100 PCS)</b>	E09KO-02060100201	0,75÷1,0	red	27,3	15	1,7	3,2	0,11
<b>KLI 2,5 (100 PCS)</b>	E09KO-02060100301	1,5÷2,5	blue	27,3	15	2,3	3,8	0,14
<b>KLI 6 (100 PCS)</b>	E09KO-02060100401	4÷6	yellow	28,0	15	3,4	5,3	0,23