Quick splice connectors, LP type

FEATURES & BENEFITS

\checkmark	facilitate electric contact with cable conductor insulation
\checkmark	facilitate branching of cable using connectors
\checkmark	connection does not require crimping tools

te electric contact with cable conductor without stripping its tion

100

LOGISTIC DATA

Quantity in package [pcs]

MECHANICAL DATA

Insulation	polyamide 6.6
Material	Cu
Surface	tin-plated
Operating temperature [°C]	-30 ÷ +95


DIMENSIONS

L 38	
W 10	

NOTE!

Suggested connector: 6.3x0.8

Туре	Index Ergom	Cross-section [mm²]	Insulation colour	Weight [kg]
LP 1 (100 PCS)	E10KN-03050100101	0,5÷1	red	0,13
LP 2,5 (100 PCS)	E10KN-03050100201	0,75÷2,5	blue	0,14
LP 6 (100 PCS)	E10KN-03050100301	4÷6	yellow	0,16



Date of publication: 22/8/2024 Graphic project, pictures and all technical data and descriptions in this catalogue are protected by Polish and international copyright laws. Names and logos used in the content of this catalogue may be trademarks, for which ZAE Ergom Sp. z o.o. has exclusive protection rights. ZAE ERGOM reserves the right for changes in the assortment and parameters of its products.

