

Insulated piggyback female push-on connectors, NWI...PCV

FEATURES & BENEFITS

- female push-on connector with male push-on connector with polyamide insulating sleeve, with long Cu sleeve inside, for double crimping
- insulating sleeve: enhances resistance to vibrations, mitigates short-circuit risk
- sleeve colours facilitate cross-section identification



LOGISTIC DATA

Quantity in package [pcs]	100
---------------------------	-----

MECHANICAL DATA


Insulation	polyvinyl chloride (PCV)
Material	brass
Surface	tin-plated
Operating temperature [°C]	-5 ÷ +60
Size	6,3x0,8

DIMENSIONS

L ₂	8,0
C	8,2

NOTE!

Terminals with PA and PC insulation available on request.



Type	Index Ergom	Cross-section [mm ²]	Insulation colour	d	L ₁	Weight [kg]
NWI 6,3-1/0,8 PCV (100 PCS)	E10KN-03010500701	0,75+1	red	1,7	22,5	0,11
NWI 6,3-2,5/0,8 PCV (100 PCS)	E10KN-03010500801	1,5+2,5	blue	2,3	22,5	0,12
NWI 6,3-6/0,8 PCV (100 PCS)	E10KN-03010500901	4+6	yellow	3,4	24,0	0,14