




FEATURES & BENEFITS

-  head with replaceable dies for system 22
-  opened hydraulic crimping head driven by separate pump
-  compact design facilitates crimping terminals in tight and limited spaces

LOGISTIC DATA

| | |
|-------------|-------------------|
| Type | GK 22 C |
| Index Ergom | E06PZ-05110001601 |
| Weight [kg] | 3 |

MECHANICAL DATA

| | |
|------------------------|--|
| Drive | external pressure source |
| Die type | KP22 |
| Crimping force [kN] | 60 |
| Working pressure [MPa] | depending on the feed pump, max. 70 |
| Piston stroke [mm] | 15 |
| Coupler type | 115 Series COUPLING 3/8" NPT MALE NBR |
| Length [mm] | 210 |
| Crimping range | 6 ÷ 300 |

NOTE!

KP22 dies must be ordered separately - we recommend ordering a complete set.

CRIMPING

| Terminal group | Cable cross-section [mm²] | Crimping shape |
|--------------------------|---------------------------|----------------|
| Al DIN | 10-240 | hexagon |
| Al-Cu | 10-240 | hexagon |
| Al-c | 16-240 | hexagon |
| Al-g | 16-185 | hexagon |
| CKOR, CKL | 10-240 | hexagon |
| Cu DIN | 6-300 | hexagon |
| Cu EKO - KREo, LE | 10-240 | hexagon |
| H...ERHN, HI...ERHL, HIG | 10-185 | trapezoid |
| HI 2x | 6-16 | trapezoid |
| KO, KW, KI, KOR, KL | 10-95 | indent |
| KOI, KWI, KII, KLI | 10-120 | oval |
| MJPB | 16-35 | hexagon |
| MJPT | 16-120 | hexagon |
| Standard Cu | 10-400 | hexagon |
| ZLA | 16-95 | crimping |
| ZLAF, ZLAFD | 25-70 | crimping |
| se | 35-300 | round forming |
| sm | 10-300 | round forming |



CE

| SET CONTAINS | Quantity included [pcs.] |
|--------------------|--------------------------|
| GK 22 C | 1 |
| Plastic case | 1 |
| Instruction manual | 1 |

