

FEATURES & BENEFITS

- ☒ head with replaceable dies for system H6
- ☒ opened hydraulic crimping head driven by separate pump
- ☒ wide range of crimped terminal diameters
- ☒ pressure force: 250 kN



LOGISTIC DATA

Type	HH-630
Index Ergom	E06PZ-05080100101
Weight [kg]	6,5

MECHANICAL DATA

Drive	external pressure source
Die type	H6
Crimping force [kN]	250
Working pressure [MPa]	depending on the feed pump, max. 70
Piston stroke [mm]	32
Coupler type	115 Series COUPLING 3/8" NPT MALE NBR
Length [mm]	260
Crimping range	10 ÷ 625

NOTE!

H6 dies must be ordered separately - we recommend ordering a complete set.

CRIMPING

Terminal group	Cable cross-section [mm²]	Crimping shape
Al DIN	70-500	hexagon
Al-Cu	70-300	hexagon
Al-c	95-240	hexagon
Al-g	50-240	hexagon
Cu DIN	16-625	hexagon
H...ERHN, HI...ERHL, HIG	10-185	trapezoid
HI 2x	4-16	trapezoid
KO, KW, KI, KOR, KL	10-240	indent
KOI, KWI, KII, KLI	10-120	oval
Standard Cu	16-625	hexagon
se	35-300	round forming
sm	10-300	round forming

SET CONTAINS

Quantity included [pcs.]

HH-630	1
Plastic case	1
Instruction manual	1