

Hydraulic punching head, HD 052 type, for plates

FEATURES & BENEFITS

- the possibility of using "NWX" system cutters; SY; WKY "
- leading "entrance" to the cutting head
- pressure force: 60 kN



LOGISTIC DATA

Type	HD-052
Index Ergom	E06WD-01030100301
Weight [kg]	3,1

MECHANICAL DATA

Drive	external pressure source
Crimping force [kN]	120
Max. thickness of material (steel) [mm]	3,2
Max. thickness of material (stainless steel) [mm]	1,5
Working pressure [MPa]	70
Piston stroke [mm]	25
Coupler type	115 Series COUPLING 3/8" NPT MALE NBR
Maximum range of punching holes: 1.5 mm/100 HB (round) [mm Ø]	12,2÷92,0
Maximum range of punching holes: 3.2 mm/100 HB (round) [mm Ø]	12,2÷63,5

SET CONTAINS	Quantity included [pcs.]	Comment
HD-052	1	-
3/8"-3/8" - 75 mm	1	Draws mandrel
3/4"-3/8" - 130 mm	1	Draws mandrel
3/4"-3/8"-35	1	Reducing sleeve
20	1	Spacer sleeve
23	1	Spacer sleeve
42	1	Spacer sleeve
Instruction manual	1	-
Plastic case	1	-