Hydraulic punching tools for plates, HD 5 H

FEATURES & BENEFITS



manually powered tool for cutting out holes in metal sheet using WY, NWY, etc. blanking dies



compact design facilitates cutting out in limited spaces and simplifies transport

LOGISTIC DATA

Туре	HD 5 H
Index Ergom	E06WD-01070001101
Weight [kg]	6,5



MECHANICAL DATA

Drive	manual
Crimping force [kN]	60
Max. thickness of material (steel) [mm]	3,2
Working pressure [MPa]	70
Piston stroke [mm]	22
Maximum range of punching holes: 1.5 mm/100 HB (round) [mm Ø]	12,2÷115,5
Maximum range of punching holes: 3.2 mm/100 HB (round) [mm Ø]	12,2÷63,5
Punched 1,5 mm/100 HB (square) hole range [mm]	92x92
Maximum range of punching holes: 3.2 mm/100 HB (square) [mm]	54x54
Maximum range of punching holes: 1,5 mm/100 HB (rectangle) [mm]	42x82
Maximum range of punching holes: 3.2 mm/100 HB (rectangular) [mm]	22x68

DIMENSIONS

1 41- P 3	000	
Length [mm]	.320	

SET CONTAINS	Quantity included [pcs.]	Comment
HD 5 H	1	-
3/4"-3/8"-35	1	Reducing sleeve
38/19-20	1	Spacer sleeve
38/19-34	1	Spacer sleeve
38/19-44	1	Spacer sleeve
3/4"-3/8" - 80 mm	1	Draw mandrel
3/4"-3/4" - 138 mm	1	Draw mandrel
Plastic case	1	
Instruction manual	1	

Date of publication:

14/12/2023

Graphic project, pictures and all technical data and descriptions in this catalogue are protected by Polish and international copyright laws. Names and logos used in the content of this catalogue may be trademarks, for which ZAE Ergom Sp. z o.o. has exclusive protection rights.

ZAE ERGOM reserves the right for changes in the assortment and parameters of its products.