

FEATURES & BENEFITS



replaceable die for system 19



crimping shape: "trapeze", "notch", "oval", "hexagon", "notched", "formed" - depending on selected die

NOTE!

On special request we can provide dies for other purposes.



Type	Index Ergom	Socket code no.	Cable cross-section [mm ²]	Terminal group	Crimping shape
K19-6	E06PZ-04040200200	6	10	Cu EKO - KREo, LE	hexagon
		6	10	Cu DIN	
K19-7	E06PZ-04040200300	7	10	Standard Cu	hexagon
		7	16	Cu EKO - KREo, LE	
K19-8	E06PZ-04040200400	8	16	Standard Cu	hexagon
		8	16	Cu DIN	
K19-9	E06PZ-04040200450	9	25	Cu EKO - KREo, LE	hexagon
K19-10	E06PZ-04040200500	10	25	Standard Cu	hexagon
		10	25	Cu DIN	
		10	16	Al-c	
		10	10	Al DIN	
K19-12	E06PZ-04040200700	12	35	Standard Cu	hexagon
		12	35	Cu DIN	
		12	35	Al-c	
		12	16-25	Al DIN	
		12	16-25	Al-Cu	
K19-13	E06PZ-04040200800	13	50	Cu EKO - KREo, LE	hexagon
		13	16	Al-g	
K19-16	E06PZ-04040201000	16	70	Standard Cu	hexagon
		16	70	Cu DIN	
		16	70	Al-c	
		16	35	Al-g	
		16	50	Al DIN	
		16	50	Al-Cu	
K19-17	E06PZ-04040201100	17	95	Standard Cu	hexagon
		17	95	Cu EKO - KREo, LE	
K19-18	E06PZ-04040201200	18	95	Al-c	hexagon
		18	50	Al-g	
		18	70	Al DIN	
		18	70	Al-Cu	
		18	95	Cu DIN	
K19-19	E06PZ-04040201300	19	120	Standard Cu	hexagon
		19	120	Al-c	
		19	120	Cu EKO - KREo, LE	
K19-20	E06PZ-04040201400	20	150	Standard Cu	hexagon
		20	150	Cu EKO - KREo, LE	
		20	120	Cu DIN	
		20	70	Al-g	
K19-23	E06PZ-04040201700	23	185	Standard Cu	hexagon
		23	185	Cu EKO - KREo, LE	
		23	185	Al-c	

Type	Index Ergom	Socket code no.	Cable cross-section [mm ²]	Terminal group	Crimping shape
K19-28	E06PZ-04040201900	28	300	Standard Cu	hexagon
		28	240	Cu DIN	
		28	240	Al-c	
		28	150	Al-g	
		28	185	Al DIN	
		28	185	Al-Cu	
K19 S16	E06PZ-04040300200	-	16	sm	round forming
K19 S35	E06PZ-04040300400	-	35	sm	round forming
		-	50	se	
K19 S50	E06PZ-04040300500	-	50	sm	round forming
		-	70	se	
K19 S70	E06PZ-04040300600	-	70	sm	round forming
		-	95	se	
K19 S95	E06PZ-04040300700	-	95	sm	round forming
		-	120	se	
K19 S120	E06PZ-04040300800	-	120	sm	round forming
		-	150	se	
K19 S150	E06PZ-04040300900	-	150	sm	round forming
		-	185	se	
K19 S185	E06PZ-04040301000	-	185	sm	round forming
		-	240	se	
K19 S240	E06PZ-04040301100	-	240	sm	round forming
		-	300	se	
K19 K50	E06PZ-04040600500	-	50	KO, KW, KI, KOR, KL	indent
K19 K95	E06PZ-04040600700	-	95	KO, KW, KI, KOR, KL	indent
K19 I120	E06PZ-04040400800	-	120	KOI, KWI, KII, KLI, NI, WI, GI, NCI, WCI, GCI (PA, PC, PCV)	oval
K19 H35	E06PZ-04040500400	-	35	H...ERHN, HI...ERHL, HIG	trapezoid
K19-ZL16	E06PZ-04040700100	-	16	ZLA	crimping
K19-ZL25	E06PZ-04040700200	-	25	ZLA	crimping
K19-ZL35	E06PZ-04040700300	-	35	ZLA	crimping
K19-ZL50	E06PZ-04040700400	-	50	ZLA	crimping
K19-ZL70	E06PZ-04040700500	-	70	ZLA	crimping
K19-ZL95	E06PZ-04040700600	-	95	ZLA	crimping
K19-ZL120	E06PZ-04040700700	-	120	ZLA	crimping