

## FEATURES & BENEFITS



crimping tool with replaceable dies for system 22



rotary and opened working head facilitates side and front "entry" to crimping head



compact design facilitates crimping in limited spaces



CE

## LOGISTIC DATA

Type	HK 22 C
Index Ergom	E06PZ-05110001251
Weight [kg]	3,2

## MECHANICAL DATA

Drive	manual
Die type	KP22
Rotate head angle [deg.]	180
Crimping force [kN]	61
Working pressure [MPa]	55
Piston stroke [mm]	15
Length [mm]	427
Crimping range	6 ÷ 300

## NOTE!

KP22 dies must be ordered separately - we recommend ordering a complete set.

## CRIMPING

Terminal group	Cable cross-section [mm²]	Crimping shape
Al DIN	10-240	hexagon
Al-Cu	10-240	hexagon
Al-c	16-240	hexagon
Al-g	16-185	hexagon
CKOR, CKL	10-240	hexagon
Cu DIN	6-300	hexagon
Cu EKO - KREo, LE	10-240	hexagon
H...ERHN, HI...ERHL, HIG	10-185	trapezoid
HI 2x	6-16	trapezoid
KO, KW, KI, KOR, KL	10-95	indent
KOI, KWI, KII, KLI	10-120	oval
MJPB	16-35	hexagon
MJPT	16-120	hexagon
Standard Cu	10-400	hexagon
ZLA	16-95	crimping
ZLAF, ZLAFD	25-70	crimping
se	35-300	round forming
sm	10-300	round forming

SET CONTAINS	Quantity included [pcs.]
HK 22 C	1
Plastic case	1
Instruction manual	1