





Hydraulic crimping tool, WHPH 2/38

FEATURES & BENEFITS

-  crimping dies for HP system
-  side crimping head "inlet"
-  non-opened crimping head
-  pressure force: 130 kN



LOGISTIC DATA

Type	WHPH2/38
Index Ergom	E06PZ-05050100200
Weight [kg]	8

The side crimping head "inlet" makes it possible to crimp terminals in difficult locations and limited working space. Replaceable crimping dies

MECHANICAL DATA

Die type	HP
Rotate head angle [deg.]	180
Head "entry" depth [mm]	38
Crimping force [kN]	130
Working pressure [MPa]	70
Piston stroke [mm]	38
Length [mm]	770
Crimping range	10 ÷ 400

CRIMPING

Terminal group	Cable cross-section [mm²]	Crimping shape
Al DIN	10-240	hexagon
Al-c	16-240	hexagon
Al-g	16-240	hexagon
Cu DIN	16-300	hexagon
Cu EKO - KREo, LE	10-95	hexagon
H...ERHN, HI...ERHL, HIG	10-185	trapezoid
HI 2x	4-16	trapezoid
KO, KW, KI, KOR, KL	10-150	indent
KOI, KWI, KII, KLI	10-120	oval
Standard Cu	16-400	hexagon
se	35-300	round forming
sm	10-300	round forming

SET CONTAINS

Quantity included [pcs.]

WHPH2/38	1
Plastic case	1
Instruction manual	1