Professional hydraulic crimping tool, HKP 22

FEATURES & BENEFITS

V

professional crimping tool with in-built pressure source

 \checkmark


replaceable dies for system 22



rotary and opened working head facilitates side and front "entry" to crimping head



two-stage hydraulic system; number of lever movements to crimp elements - $\ensuremath{\mathsf{5}}$



MECHANICAL DATA

Drive	manual	
Die type	KP22	
Rotate head angle [deg.]	180	
Crimping force [kN]	60	
Length [mm]	415	
Crimping range	6 ÷ 300	

NOTE!

KP22 dies must be ordered separately - we recommend ordering a complete set.

CRIMPING

Terminal group	Cable cross-section [mm ²]	Crimping shape
AI DIN	10-240	hexagon
Al-Cu	10-240	hexagon
Al-c	16-240	hexagon
Al-g	16-185	hexagon
CKOR, CKL	10-240	hexagon
Cu DIN	6-300	hexagon
Cu EKO - KREo, LE	10-240	hexagon
HERHN, HIERHL, HIG	10-185	trapezoid
HI 2x	6-16	trapezoid
KO, KW, KI, KOR, KL	10-95	indent
KOI, KWI, KII, KLI	10-120	oval
МЈРВ	16-35	hexagon
MJPT	16-120	hexagon
Standard Cu	10-400	hexagon
ZLA	16-95	crimping
ZLAF, ZLAFD	25-70	crimping
se	35-300	round forming
sm	10-300	round forming





 ϵ

Graphic project, pictures and all technical data and descriptions in this catalogue are protected by Polish and international copyright laws.

Names and logos used in the content of this catalogue may be trademarks, for which ZAE Ergom Sp. z o.o. has exclusive protection rights.

ZAE ERGOM reserves the right for changes in the assortment and parameters of its products.

11/7/2024

publication:

SET CONTAINS	Quantity included [pcs.]	
HKP 22	1	
Metal case	1	
Instruction manual	1	



