Professional hydraulic crimping tool, HKP 5 D

FEATURES & BENEFITS

professional crimping tool with replaceable dies for system 5
rotary and opened working head facilitates side and front "entry" to crimping head
compact design facilitates crimping in limited spaces

LOGISTIC DATA

Туре	HKP 5 D
Index Ergom	E06PZ-05120011201
Weight [kg]	2,3

MECHANICAL DATA

Drive	manual
Die type	НК5/НКР5
Rotate head angle [deg.]	180
Head "entry" depth [mm]	5
Crimping force [kN]	55
Working pressure [MPa]	55
Number of hydraulic system stages	1
Piston stroke [mm]	13
Length [mm]	380
Crimping range	6 ÷ 300

P Tools rofessional

CE

NOTE!

 $\ensuremath{\mathsf{HK5}}$ dies must be ordered separately - we recommend ordering a complete set.

CRIMPING

Terminal group	Cable cross-section [mm ²]	Crimping shape
AI DIN	10-150	hexagon
Al-c	16-185	hexagon
Al-g	16-120	hexagon
Cu DIN	6-185	hexagon
Cu EKO - KREo, LE	10-120	hexagon
HERHN, HIERHL, HIG	50-150	trapezoid
HI 2x	16	trapezoid
KO, KW, KI, KOR, KL	10-35	indent
KOI, KWI, KII, KLI	70	oval
Standard Cu	16-240	hexagon
ZLA	16-120	crimping
se	50-240	round forming
	35-185	round forming

SET CONTAINS	Quantity included [pcs.]
HKP 5 D	1
Plastic case	1
Instruction manual	1

Date of 11/7/2024 publication:

Graphic project, pictures and all technical data and descriptions in this catalogue are protected by Polish and international copyright laws. Names and logos used in the content of this catalogue may be trademarks, for which ZAE Ergom Sp. z o.o. has exclusive protection rights. ZAE ERGOM reserves the right for changes in the assortment and parameters of its products.



www.ergom.com