Battery-powered professional hydraulic mini crimping tool, HKP 5 MEL

FEATURES & BENEFITS

professional crimping tool with replaceable dies for system 5

rotary and opened working head facilitates side and front "entry" to crimping head



automatic return of the piston and two-stage hydraulic system



software for crimping operation analysis

LOGISTIC DATA

Туре	HKP 5 MEL
Index Ergom	E06PZ-05160005051
Weight [kg]	2,3

Battery-powered professional hydraulic crimping tool with the built-in pressure

Sattery-powered professional nydraulic crimping tool with the built-in pressure source in the vertical configuration.

An automatic safety valve, "slowing down" the pressure after reaching the maximum level in the pump. A two-stage hydraulic system assuring quick stroke and slow working movement to use its full strength. A possibility to set the required pressure and the time of tightening and pressure release. Equipped with analytic PC software. Guaranteed 10,000 working cycles of the tool (a service incontion required after this period). service inspection required after this period).

MECHANICAL DATA

Drive	Battery, Li-Ion 18 V 1.5 Ah
Die type	HK5
Rotate head angle [deg.]	360
Crimping force [kN]	50
Length [mm]	370
Crimping range	6 ÷ 300

ELECTRICAL DATA

Battery charging time [min]	30	
Number of crimps from one battery charge [pcs]	approx. 170 for 150 mm² Cu standard (approximate value depends on the type of wire and tip, ambient temperature, etc.)	
Battery voltage [V]	18	
Battery capacity [mAh]	1500	

NOTE!

Continuous device operation ensured by the MEL - HE3 - PA5 mains power

HK5 dies must be ordered separately - we recommend ordering a complete







publication:

11/7/2024

Graphic project, pictures and all technical data and descriptions in this catalogue are protected by Polish and international copyright laws. Names and logos used in the content of this catalogue may be trademarks, for which ZAE Ergom Sp. z o.o. has exclusive protection rights.

ZAE ERGOM reserves the right for changes in the assortment and parameters of its products.

CRIMPING

Terminal group	Cable cross-section [mm ²]	Crimping shape
AI DIN	10-150	hexagon
Al-c	16-185	hexagon
Al-g	16-120	hexagon
Cu DIN	6-185	hexagon
Cu EKO - KREo, LE	10-120	hexagon
HERHN, HIERHL, HIG	50-150	trapezoid
HI 2x	16	trapezoid
KO, KW, KI, KOR, KL	10-35	indent
KOI, KWI, KII, KLI	70	oval
Standard Cu	16-240	hexagon
ZLA	16-120	crimping
se	50-240	round forming
sm	35-185	round forming

SET CONTAINS	Quantity included [pcs.]	Comment
HKP 5 MEL	1	-
HKP 5 MEL	1	Battery
MEL-HE3 - CHA5	1	Charger
Metal case	1	-
Instruction manual	1	-
USB cable	1	-
PC software	1	-