Insert, 68x68 mm, FL 21W11 type

FEATURES & BENEFITS

	any set-up of inserts on cable plate
\checkmark	low costs of electric system modernisation
	dedicated to FL 21R frames

LOGISTIC DATA

Туре	FL 21W11 (10 PCS)
Index Ergom	R30RS-04070001101
Quantity in package [pcs]	10



MECHANICAL DATA

Material	polypropylene reinforced with glass fibre and TPE elastomer, halogen-free
Operating temp. [°C]	-20 ÷ +125
Assembly	With snap-fasteners for FL 21R frame
Cable diameter [mm]	2x8÷17 mm (M25) 2x5÷10 mm (M16)

CERTIFICATES & STANDARDS

IP degree of protection	IP65 (with and without cables installed)
Standards	EN 60529:1991+A1; EN 60670-1:2005

NOTE!

After removing the flexible membrane from the hole, it is possible to fix a polyamide gland (e.g. DP-EN..HM) or rubber gland (e.g. PDE) - flexible glands, M16 and M25 size.

Date of 26/8/2024 publication:

Graphic project, pictures and all technical data and descriptions in this catalogue are protected by Polish and international copyright laws. Names and logos used in the content of this catalogue may be trademarks, for which ZAE Ergom Sp. z o.o. has exclusive protection rights. ZAE ERGOM reserves the right for changes in the assortment and parameters of its products.

