

Single-circuit connector ZJUN-150 type: for 150 mm² wires 1000V

FEATURES & BENEFITS

- ✓ current circuit made of tin-plated aluminium alloy
- ✓ mounting to TSE 35 rail or floor
- ✓ compact size
- ✓ screws coated with contact paste

LOGISTIC DATA

Quantity in package [pcs]	5
Weight [g]	790

MECHANICAL DATA

Current circuit element material	Al-alloy
Body material	polyamide
Cover material	polyamide
Clamp material	Al-alloy
Circuit insulation length [mm]	30
Terminal crimping shape on cord	trapezoid
Number of tracks	1
Number of screws [pcs]	2
Max. tightening torque (mounting bolt) [Nm]	30
Nominal cross-section [mm ²]	150
Wire cross-section (wire/cord), from ... to ... [mm ²]	35÷150 / 35÷150
Dimension (H x W x D) [mm]	97 x 29 x 29
Max. recommended tightening torque [Nm]	30
Recommended screwdriver tip type (hexagonal)	HEX: M8

ELECTRICAL DATA

Continuous current Al [A]	290
Continuous current Cu [A]	320
Rated insulation voltage U _i [V]	1000
Electric strength [kV]	3

CERTIFICATES & STANDARDS

IP degree of protection	IP20
Flammability class	UL 94 V0
Standards	EN 60947-7-1

NOTE!



Type	Index Ergom	Colour
ZJUN-150 (5 PCS)	R34RR-07010001903	grey
ZJUN-150/BL (5 PCS)	R34RR-07010002903	blue
ZJUN-150 PE (5 PCS)	R34RR-07020001903	yellow-green

