

Single-circuit connector ZJUN-95 type: for 95 mm² wires 1000V

FEATURES & BENEFITS

- ✓ current circuit made of tin-plated aluminium alloy
- ✓ mounting to TSE 35 rail or floor
- ✓ can be mounted under modular equipment covers
- ✓ screws coated with contact paste



LOGISTIC DATA

Quantity in package [pcs]	8
Weight [g]	736



MECHANICAL DATA

Current circuit element material	Al-alloy
Body material	polyamide
Cover material	polyamide
Clamp material	Al-alloy
Circuit insulation length [mm]	27
Terminal crimping shape on cord	trapezoid
Number of tracks	1
Number of screws [pcs]	2
Max. tightening torque (mounting bolt) [Nm]	20
Nominal cross-section [mm ²]	95
Wire cross-section (wire/cord), from ... to ... [mm ²]	16+95 / 16+95
Dimension (H x W x D) [mm]	88 x 50 x 24
Max. recommended tightening torque [Nm]	20
Recommended screwdriver tip type (hexagonal)	HEX: M5

ELECTRICAL DATA

Continuous current I _I [A]	220
Continuous current I _u [A]	245
Rated insulation voltage U _i [V]	1000
Electric strength [kV]	3

CERTIFICATES & STANDARDS

IP degree of protection	IP20
Flammability class	UL 94 V0
Standards	EN 60947-7-1

NOTE!

Type	Index Ergom	Colour
ZJUN-95 (8 PCS)	R34RR-07010001803	grey
ZJUN-95/BL (8 PCS)	R34RR-07010002803	blue
ZJUN-95 PE (8 PCS)	R34RR-07020000803	yellow-green

