

# Double-circuit connector, ZJUN-2x95 type: for 95 mm<sup>2</sup> wires 1000V

## FEATURES & BENEFITS



current circuit made of tin-plated aluminium alloy



mounting only on TSE 35 rail



can be mounted under modular equipment covers



screws coated with contact paste



## LOGISTIC DATA

Quantity in package [pcs]	3
Weight [g]	498



## MECHANICAL DATA

Current circuit element material	Al-alloy
Body material	polyamide
Cover material	polyamide
Clamp material	Al-alloy
Circuit insulation length [mm]	27
Terminal crimping shape on cord	trapezoid
Number of tracks	2
Number of screws [pcs]	4
Max. tightening torque (mounting bolt) [Nm]	20
Nominal cross-section [mm <sup>2</sup> ]	95
Wire cross-section (wire/cord), from ... to ... [mm <sup>2</sup> ]	16÷95 / 16÷95
Dimension (H x W x D) [mm]	88 x 50 x 42
Max. recommended tightening torque [Nm]	20
Recommended screwdriver tip type (hexagonal)	HEX: M5

## ELECTRICAL DATA

Continuous current Al [A]	220
Continuous current Cu [A]	245
Rated insulation voltage U <sub>i</sub> [V]	1000
Electric strength [kV]	3

## CERTIFICATES & STANDARDS

IP degree of protection	IP20
Flammability class	UL 94 V0
Standards	EN 60947-7-1

## NOTE!

Type	Index Ergom	Colour
ZJUN-2x95 (3 PCS)	R34RR-07010021303	grey
ZJUN-2x95/BL (3 PCS)	R34RR-07010021403	blue
ZJUN-2x95 PE (3 PCS)	R34RR-07020002103	yellow-green

