

# Triply-circuit connector, ZJUN-3x150 type: for 150 mm<sup>2</sup> wires 1000V

## FEATURES & BENEFITS

- ✓ current circuit made of tin-plated aluminium alloy
- ✓ mounting to TSE 35 rail or floor
- ✓ compact size
- ✓ screws coated with contact paste



## LOGISTIC DATA

Quantity in package [pcs]	1
Weight [g]	410



## MECHANICAL DATA

Current circuit element material	Al-alloy
Body material	polyamide
Cover material	polyamide
Clamp material	Al-alloy
Circuit insulation length [mm]	30
Terminal crimping shape on cord	trapezoid
Number of tracks	3
Number of screws [pcs]	6
Max. tightening torque (mounting bolt) [Nm]	30
Nominal cross-section [mm <sup>2</sup> ]	150
Wire cross-section (wire/cord), from ... to ... [mm <sup>2</sup> ]	35+150 / 35+150
Dimension (H x W x D) [mm]	98 x 59 x 73
Max. recommended tightening torque [Nm]	30
Recommended screwdriver tip type (hexagonal)	HEX: M8

## ELECTRICAL DATA

Continuous current $I_l$ [A]	290
Continuous current $I_u$ [A]	320
Rated insulation voltage $U_i$ [V]	1000
Electric strength [kV]	3

## CERTIFICATES & STANDARDS

IP degree of protection	IP20
Flammability class	UL 94 V0
Standards	EN 60947-7-1

## NOTE!

Type	Index Ergom	Colour
ZJUN-3x150	R34RR-07010022301	grey
ZJUN-3x150/BL	R34RR-07010022401	blue
ZJUN-3x150 PE	R34RR-07020002601	yellow-green

