

Triply-circuit connector, ZJUN-3x240 type: for 240 mm² wires 1000V

FEATURES & BENEFITS

- ✓ current circuit made of tin-plated aluminium alloy
- ✓ mounting only to floor
- ✓ compact size
- ✓ screws coated with contact paste



LOGISTIC DATA

Quantity in package [pcs]	1
Weight [g]	780



MECHANICAL DATA

Current circuit element material	Al-alloy
Body material	polyamide
Cover material	polyamide
Clamp material	Al-alloy
Circuit insulation length [mm]	43
Terminal crimping shape on cord	trapezoid
Number of tracks	3
Number of screws [pcs]	6
Max. tightening torque (mounting bolt) [Nm]	45
Nominal cross-section [mm ²]	240
Wire cross-section (wire/cord), from ... to ... [mm ²]	35+240 / 35+240
Dimension (H x W x D) [mm]	131 x 67 x 93
Max. recommended tightening torque [Nm]	45
Recommended screwdriver tip type (hexagonal)	HEX: M8

ELECTRICAL DATA

Continuous current Al [A]	380
Continuous current Cu [A]	425
Rated insulation voltage U _i [V]	1000
Electric strength [kV]	3

CERTIFICATES & STANDARDS

IP degree of protection	IP20
Flammability class	UL 94 V0
Standards	EN 60947-7-1

NOTE!

Type	Index Ergom	Colour
ZJUN-3x240	R34RR-07010022501	grey
ZJUN-3x240/BL	R34RR-07010022601	blue
ZJUN-3x240 PE	R34RR-07020002701	yellow-green

